

Zhejiang Huaneng Micro Bearing Co,.Ltd.

Bearing Pulley Hardware Manufacturer

Address: No. 118, Development Road, Wengyang Industrial Zone, Yueqing City, Zhejiang Province,

China

Tel/WA: +86-15058997617 (Shirley Ying)

Email: hune@cnhune.com

shirley@cnhune.com

Website: www.hunepulley.com











Catalog

- Company Profile
- Factory Advantages
- Customization
- Products Display
- Contact



Company Profile




As Chinese Bearing Pulley Manufacturers and Miniature Bearings Factory, we specialize in the development and manufacturing of miniature and medium-sized bearings, non-standard bearings, and pulley systems.

With over a decade of industry experience, we offer high-precision processing and responsive customization services. Our products are widely used in home appliances, industrial equipment, and door and window systems, and are exported to Japan, Korea, Europe, and other regions.

We are specialized in **OEM and ODM** production.Our mission is to meet customer's expectation by providing high quality products and on time delivery.



Market Distribution



Main
export
regions:
Japan
Korea
Europe
USA
Southeast
Asia

Our Advantages

Industrial Scale Advantage

Production Quality
Advantage

Product Quality Advantage Technological Cooperation Advantage



Three major industries (bearings, pulleys, hardware); its scale brings advantages in production capacity and resource integration, with favorable and competitive prices offered.

20+ years in bearing production; ISO9001-certified; Self-operated import/export rights; Standardized management ensuring compliance with international trade standards.

Our bearing products lead the domestic industry, with stable, reliable quality. Made of high-quality materials, with exquisite craftsmanship, automated equipment, they focus on low-noise, long-life bearings. Strong technical capabilities; Established technical collaboration with domestic research institutions; Advanced production equipment and scientific testing methods ensure high-quality product output.







| \\/\\/\\/ | hunenu | lley.com |
|---------------|----------|-------------|
| V V V V V V . | 11011000 | 110 9.00111 |

| Plastic | POM, POK,Nylon 6/66, PU, Rubber, and customized to customer requirements |
|---------------------|--|
| Accuracy | ABEC-1, ABEC-3, ABEC-7 |
| Diametral clearance | Standard classes C2, C0, C3, C4 or customized to customer requirements |
| Quality control | Dynamic load rating (Cr) and rating life comply with ISO281/1; static load rating (Cor) aligns with ISO76. |
| Performance | Low-Noise Operation, Slide Smoothly, Durability, Lightweight, Long-Life Use, weather resistance |











Plastic-coated pulleys typically consist of a base material and a coated plastic layer, each contributing specific properties to the overall performance. All can be customized to meet your requirments.

Plastic Material

| Material | Best For | Max Temperature | Weight Capacity | Cost | |
|---------------|---|-----------------|-----------------|-------------|--|
| Polypropylene | Light loads, damp areas | 80° C | Low | Low | |
| Nylon | General use, moderate loads | 100° C | Medium | Medium | |
| Acetal | Smooth spinning, moisture resistance | 120° C | Medium-High | Medium-High | |
| Polyester | High heat, chemicals, heavy loads | 150° C | High | High | |

Bearing Material

| Material | Chromium Content | Hardness (Rockwell C) | Rust Resistance | Best For | Cost |
|-----------------|----------------------|-----------------------|-----------------|---|-------------|
| Bearing Steel | 0.3-1.0% | 60-64 | Low | Light to medium loads, dry environments | Low-Medium |
| Chrome Steel | 1.3-1.6% | 62-66 | Low-Medium | Heavy loads, high speed, dry setups | Medium |
| Stainless Steel | 10.5%+ (plus nickel) | 50-55 | High | Wet/damp areas, food-safe setups | Medium-High |

Why Choose Us











Reliable Support

Quick response and clear communication from first contact to delivery.

Custom Fit

Flexible solutions tailored to your structure, space, and function needs.

Trusted Delivery

From samples to mass production, we make things happen — fast and right.

Free Samples

Try before you buy — fast sample support to help you make confident decisions.

After-sale Service Providing professional technical knowledge to solve product problems.Offer the

replacement, Other










Cooperative Partners














Manufacturing Process

Our micro pulley manufacturing combines advanced CNC machining and high-precision molding to produce durable, lightweight components with tolerances within ±0.01mm.







Main Facilities List

| Facility Name | Qty |
|----------------------------|-----|
| Injection moulding Machine | 8 |
| Large Punch press | 5 |
| Small Punch press | 8 |
| Lathe | 6 |
| CNC | 4 |
| Grinder Machine | 4 |





PROCESS FLOW



Over the years, we have accumulated a great deal of experience in customising miniature bearings, pulleys, lifting wheels and other products for special structures, small spaces, high environmental stress and other working conditions. We collaborate with our customers' engineers to develop and quickly respond to the needs, providing complete personalised solutions from structural optimisation, material selection to performance testing.

Design

Support customer drawings / samples reverse modelling, can also be based on the structure and use of the demand for design proposals.

Material

Carbon steel, stainless steel, plastic, copper, composite materials and other combinations of customisation.

Structure

Flexible customisation of dimensions, installation methods, dustproof structure, sealing level and other parameters.

Multi-scenario


Experienced in solving problems under tight space constraints, complex setups, unusual loads, and harsh environments.


Sampling


Support rapid sampling and small amount of trial production, which is convenient for customers to carry out preverification.













R-shaped Pulley



U-shaped Pulley



Y-shaped Pulley

Plastic Bearing Pulley



Screw Thread Pulley



F-shaped Pulley



H-shaped Pulley



Non-Standard Pulley



V-shaped Pulley









Door & Window Roller Hardware Accessories

















LHUNE

























| 轴承型号 | 外形尺寸 Shape dimenion | | | | | | | | 钢球 Steel Balls | | 额定负荷 Load Rating | | 参考 |
|---------------|------------------------|--------|-----|--------------------|-----|--------------------|-----|--------------------------|-------------------|--------|---------------------|-----------------|--------|
| Bearing NO | 内径 d mm inch | | *** | 外径 D mm inch | | 宽度 B mm inch | | 倒角 Chamfer mm inch | | Size | 动负荷 Cr N | 静负荷 Cor N | or kg |
| 604 | 4 | 0.1575 | 12 | 0.4724 | 4 | 0.1575 | 0.2 | 0.008 | 6 | 2.381 | 970 | 360 | 0.0023 |
| 605 | 5 | 0.1969 | 14 | 0.5512 | 5 | 0.1969 | 0.2 | 0.008 | 6 | 3.175 | 1300 | 505 | 0.0037 |
| 606 | 6 | 0.2362 | 17 | 0.6693 | 6 | 0.2362 | 0.3 | 0.012 | 6 | 3.175 | 2260 | 836 | 0.0069 |
| 607 | 7 | 0.2756 | 19 | 0.748 | 6 | 0.2360= | 0.3 | 0.012 | 7 | 3.5 | 2340 | 885 | 0.0082 |
| 608 | 8 | 0.315 | 22 | 0.8661 | 7 | 0.2756 | 0.3 | 0.012 | 7 | 3.969 | 3300 | 1370 | 0.0129 |
| 609 | 9 | 0.3543 | 24 | 0.9949 | 7 | 0.2756 | 0.3 | 0.012 | 7 | 3.969 | 3350 | 1430 | 0.016 |
| 6000 | 10 | 0.3937 | 26 | 1.0236 | 8 | 0.315 | 0.3 | 0.012 | 7 | 4.763 | 4160 | 1780 | 0.019 |
| 6001 | 12 | 0.4724 | 28 | 1.1024 | - 8 | 0.315 | 0.3 | 0.012 | 8 | 4.763 | 5110 | 2370 | 0.022 |
| 6002 | 15 | 0.5906 | 32 | 1.2598 | 9 | 0.3543 | 0.3 | 0.012 | 9 | 4.763 | 5590 | 2840 | 0.03 |
| 6003 | 17 | 0.6693 | 35 | 1.378 | 10 | 0.3937 | 0.3 | 0.012 | 8 | 6.747 | 6000 | 3250 | 0.039 |
| 6004 | 20 | 0.7874 | 42 | 1.6535 | 12 | 0.4735 | 0.6 | 0.024 | 8 | 7.938 | 9390 | 5020 | 0.069 |
| 6005 | 25 | 0.9843 | 47 | 1.8504 | 12 | 0.4724 | 0.6 | 0.024 | 9 | 7.938 | 10060 | 5860 | 0.08 |
| 6006 | 30 | 1.1811 | 55 | 2.1654 | 13 | 0.5118 | 1 | 0.039 | 9 | 9.525 | 11900 | 7460 | 0.116 |
| 6007 | 35 | 1.378 | 62 | 2.4409 | 14 | 0.5512 | 1 | 0.039 | 9 | 11.112 | 16210 | 10420 | 0.115 |
| 6008 | 40 | 1.5748 | 68 | 2.6772 | 15 | 0.5906 | 1 | 0.039 | 9 | 12 | 17030 | 11700 | 0.192 |
| 6009 | 45 | 1.7717 | 75 | 2.9528 | 16 | 0.6299 | 1 | 0.039 | 10 | 12 | 21080 | 14780 | 0.245 |
| 6010 | 50 | 1.9685 | 80 | 3.1496 | 16 | 0.6299 | 1 | 0.039 | 10 | 12.7 | 22000 | 16260 | 0.261 |
| 6011 | 55 | 2.1653 | 90 | 3.5433 | 18 | 0.7086 | 1.1 | 0.043 | 10 | 14.288 | 23280 | 17860 | 0.362 |
| 6012 | 60 | 2.3622 | 95 | 3.7401 | 18 | 0.7086 | 1.1 | 0.043 | 10 | 15.081 | 24350 | 19350 | 0.385 |
| 6013 | 65 | 2.559 | 100 | 3.937 | 18 | 0.7086 | 1.1 | 0.043 | | | 29680 | 24200 | 0.41 |



Canton Fair Exihibition Attending







Project Discussion





Quality Inspection







HUNE















Contact me



ShirleyYing

SalesManager Zhejiang Hune Micro Bearing Co,.Ltd

- +8615058997617
- Shirley@cnhune.com
- 118FazhanRoad, Yueqing, Zhejiang, China

Wechat QR Code



What's app QR Code





Address:

No. 118, Development Road, Wengyang Industrial Zone, Yueqing City, Zhejiang Province, China